

according to Regulation (EC) No 1907/2006

Primo Adhesive

Revision date: 18.12.2020

Product code: 10227

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Primo Adhesive

UFI: 21AW-E0PY-E00E-V691

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive for denture relinings for use in dentistry.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name:	DETAX GmbH & Co. KG	
Street:	Carl-Zeiss-Strasse	
Place:	D-76275 Ettlingen	
Telephone:	+49 7243/510-0	Telefax: +49 7243/510-100
e-mail:	post@detax.de	
Internet:	www.detax.de	
Responsible Department:	Emergency number:	
	+49 7243/510-0	
	This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)	

Importer / Distributer

Company name:	Durodent Dental Supplies
Place:	Unit 6 / 51 Jersey Road, Bayswater, VIC 3153 AUS
Telephone:	+ 61 (03) 9720 6700
e-mail:	sales@durodent.com.au
Responsible Department:	For non-urgent inquiries refer to:
	Durodent Dental Supplies (Office) Phone: (03) 97206700
	This number is only available during the following office hours:
	Mon-Thurs 09:00am - 5:00pm / Friday 09:00am - 4.30pm AEST
	Australian Poisons Information Centre (National) 13 11 26 - 24 Hours / 7 Days

1.4. Emergency telephone number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
 Flammable liquid: Flam. Liq. 2
 Hazard Statements:
 Highly flammable liquid and vapour.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.

according to Regulation (EC) No 1907/2006

Primo Adhesive

Revision date: 18.12.2020

Product code: 10227

Page 2 of 8

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P370+P378	In case of fire: Use Carbon dioxide (CO ₂), Foam, Extinguishing powder to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container to according to local and applicable legislation of dispose of waste.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of alkoxysilane derivatives.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

according to Regulation (EC) No 1907/2006

Primo Adhesive

Revision date: 18.12.2020

Product code: 10227

Page 3 of 8

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

No special measures are necessary.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Adhesive for silicone based denture relinings.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.2. Exposure controls****Protective and hygiene measures**

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is

Primo Adhesive

Revision date: 18.12.2020

Product code: 10227

Page 4 of 8

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber)

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid:
Colour:	colourless
Odour:	aromatic

Test method

pH-Value:	not determined
-----------	----------------

Changes in the physical state

Melting point:	not determined
----------------	----------------

Initial boiling point and boiling range:	135-140 °C	DIN 51356
--	------------	-----------

Flash point:	12 °C	DIN 51755
--------------	-------	-----------

Flammability

Solid:	not applicable
--------	----------------

Gas:	not applicable
------	----------------

Lower explosion limits:	not determined
-------------------------	----------------

Upper explosion limits:	not determined
-------------------------	----------------

Ignition temperature:	>260 °C	DIN 51794
-----------------------	---------	-----------

Auto-ignition temperature

Solid:	not applicable
--------	----------------

Gas:	not applicable
------	----------------

Decomposition temperature:	>120 °C
----------------------------	---------

Oxidizing properties

Not oxidizing.

Vapour pressure:	2,5 hPa
------------------	---------

(at 20 °C)

Vapour pressure:	1100 hPa
------------------	----------

(at 50 °C)

Density (at 20 °C):	0,94 g/cm ³	DIN 51757
---------------------	------------------------	-----------

Water solubility:	insoluble
-------------------	-----------

Solubility in other solvents

not determined

Partition coefficient:	not determined
------------------------	----------------

Viscosity / dynamic:	1,3 mPa·s	BROOKFIELD
----------------------	-----------	------------

(at 23 °C)

Vapour density:	not determined
-----------------	----------------

Evaporation rate:	not determined
-------------------	----------------

9.2. Other information

Solid content:	not determined
----------------	----------------

according to Regulation (EC) No 1907/2006

Revision date: 18.12.2020

Primo Adhesive

Product code: 10227

Page 5 of 8

SECTION 10: Stability and reactivity**10.1. Reactivity**

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with : oxidising agents, spontaneously flammable or combustible materials. Slow decomposition in water.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

In case of hydrolysis, methanol is released.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

For the product itself no toxicological data are available. In products with a comparable composition, a LD50 (orally, species rat) of > 5000 mg/kg has been found. In products with a comparable composition a LD50 (intracutaneous, species rabbit) of >2000 mg/kg has been found.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

The product is not: Ecotoxic.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Not identified as PBT/ vPvB substances

according to Regulation (EC) No 1907/2006

Primo Adhesive

Revision date: 18.12.2020

Product code: 10227

Page 6 of 8

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1866
14.2. UN proper shipping name:	Resin solution
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Other applicable information (land transport)

Flammable liquid

Marine transport (IMDG)

14.1. UN number:	UN 1866
14.2. UN proper shipping name:	Resin solution
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Marine pollutant:	-
Special Provisions:	-
Limited quantity:	5 L/ 30 kg
EmS:	F-E, S-E

Other applicable information (marine transport)

Flash point: 12°C c.c.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1866
14.2. UN proper shipping name:	Resin solution
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	1 L/ 30 kg
Passenger LQ:	Y341
IATA-packing instructions - Passenger:	353

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primo Adhesive

Revision date: 18.12.2020

Product code: 10227

Page 7 of 8

IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Gewerblich	-	-	-	-	-	-	-	2

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Primo Adhesive

Revision date: 18.12.2020

Product code: 10227

Page 8 of 8

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)