

according to Regulation (EC) No 1907/2006

freeprint® cast 385

Revision date: 17.12.2020

Product code: 11089

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

freeprint® cast 385

UFI: 9FSY-W009-000V-K0WF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Ligth-curing resin for the generative fabrication of cast objects using precision casting technology

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name:	DETAX GmbH & Co. KG	
Street:	Carl-Zeiss-Strasse	
Place:	D-76275 Ettlingen	
Telephone:	+49 7243/510-0	Telefax: +49 7243/510-100
e-mail:	post@detax.de	
Internet:	www.detax.de	
Responsible Department:	Emergency number:	
	+49 7243/510-0	
	This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. - 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)	

Importer / Distributer

Company name:	Durodent Dental Supplies
Place:	Unit 6 / 51 Jersey Road, Bayswater, VIC 3153 AUS
Telephone:	+ 61 (03) 9720 6700
e-mail:	sales@durodent.com.au
Responsible Department:	For non-urgent inquiries refer to:
	Durodent Dental Supplies (Office) Phone: (03) 97206700
	This number is only available during the following office hours:
	Mon-Thurs 09:00am - 5:00pm / Friday 09:00am – 4.30pm AEST
	Australian Poisons Information Centre (National) 13 11 26 – 24 Hours / 7 Days

1.4. Emergency telephone number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

- Serious eye damage/eye irritation: Eye Irrit. 2
- Respiratory or skin sensitisation: Skin Sens. 1
- Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

- Causes serious eye irritation.
- May cause an allergic skin reaction.
- Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

according to Regulation (EC) No 1907/2006

freeprint® cast 385

Revision date: 17.12.2020

Product code: 11089

Page 2 of 11

Hazard components for labelling

aliphatic urethane acrylate
tripropylene glycol diacrylate
tetrahydrofurfuryl methacrylate THFMA purified grade
diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/ container in accordance with local and national regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of acrylic/ methacrylic resins with auxilliary matters.

according to Regulation (EC) No 1907/2006

freeprint® cast 385

Revision date: 17.12.2020

Product code: 11089

Page 3 of 11

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
	acrylated resin			10-40 %
	Eye Irrit. 2; H319			
108-32-7	propylene carbonate			10-30 %
	203-572-1	607-194-00-1	01-2119537232-48	
	Eye Irrit. 2; H319			
	aliphatic urethane acrylate			1-10 %
	906-949-5		01-2120266262-60	
	Skin Sens. 1B, Aquatic Chronic 2; H317 H411			
42978-66-5	tripropylene glycol diacrylate			1-10 %
	256-032-2		01-2119484613-34	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 2; H315 H319 H317 H335 H411			
2455-24-5	tetrahydrofurfuryl methacrylate THFMA purified grade			1-15 %
	Repr. 2, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H361 H315 H319 H317 H335			
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			0,1-5 %
	278-355-8	015-203-00-X		
	Repr. 2, Skin Sens. 1B, Aquatic Chronic 2; H361f H317 H411			
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide			0,1-5 %
	423-340-5	015-189-00-5	01-2119489401-38	
	Skin Sens. 1, Aquatic Chronic 4; H317 H413			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water.

Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

according to Regulation (EC) No 1907/2006

freeprint® cast 385

Revision date: 17.12.2020

Product code: 11089

Page 4 of 11

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

No special measures are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed.

Hints on joint storage

Keep away from spontaneous flammable or combustible substances.

Further information on storage conditions

Keep only in the original container in a dry and well-ventilated place, away from foodstuffs. Keep away from all kind of lighth. An inert gas blanket should not be applied, because the stability of the product depends on the presence of oxygen (air).

7.3. Specific end use(s)

Lighth-curing resin for the generative fabrication of cast objects using precision casting technology

For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

according to Regulation (EC) No 1907/2006

freeprint® cast 385

Revision date: 17.12.2020

Product code: 11089

Page 5 of 11

8.2. Exposure controls

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber)

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	red - transparent
Odour:	faintly like esters

Test method

pH-Value:	not determined
-----------	----------------

Changes in the physical state

Melting point:	not determined
----------------	----------------

Initial boiling point and boiling range:	not determined
------------------------------------------	----------------

Flash point:	>100 °C DIN 51755
--------------	-------------------

Flammability

Solid:	not determined
--------	----------------

Gas:	not applicable
------	----------------

Lower explosion limits:	not determined
-------------------------	----------------

Upper explosion limits:	not determined
-------------------------	----------------

Auto-ignition temperature

Solid:	not determined
--------	----------------

Gas:	not applicable
------	----------------

Decomposition temperature:	>=190 °C
----------------------------	----------

Oxidizing properties

Not oxidizing.

Vapour pressure: (at 20 °C)	<1 hPa
--------------------------------	--------

Density (at 20 °C):	1,12 g/cm³ DIN 51757
---------------------	----------------------

Water solubility:	practically insoluble
-------------------	-----------------------

Solubility in other solvents

not determined

according to Regulation (EC) No 1907/2006

freeprint® cast 385

Revision date: 17.12.2020

Product code: 11089

Page 6 of 11

Partition coefficient:	not determined
Vapour density:	not determined
Evaporation rate:	not determined

9.2. Other information

Solid content:	not determined
----------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with : strong oxidising agents, strong alkaline or acidic materials.

10.4. Conditions to avoid

oxidising agents, radicals forming substances or heavy metal ions. Ultra-violet light and daylight initiate polymerisation of the product. Therefore keep only in tightly closed containers away from any sources of light at 15°C - 28°C / 59°F - 82 °F.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

In case of fire, acrid acrylic fumes may occur.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

For the product itself no toxicological data are available. In products with a comparable composition, a LD50 (orally, species rat) of > 5000 mg/kg has been found.

according to Regulation (EC) No 1907/2006

freeprint® cast 385

Revision date: 17.12.2020

Product code: 11089

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	acrylated resin				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
108-32-7	propylene carbonate				
	oral	LD50 34600 mg/kg	Rat	GESTIS	
	dermal	LD50 > 23800 mg/kg	Rabbit	GESTIS	
	aliphatic urethane acrylate				
	oral	LD50 >5000 mg/kg	Rat	OECD 401	
42978-66-5	tripropylene glycol diacrylate				
	oral	LD50 6200 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide				
	oral	LD50 >2000 mg/kg	Rat	OECD 401	
	dermal	LD50 >2000 mg/kg	Rat	OECD 402	

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (aliphatic urethane acrylate; tripropylene glycol diacrylate; tetrahydrofurfuryl methacrylate THFMA purified grade; diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide; phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

according to Regulation (EC) No 1907/2006

freeprint® cast 385

Revision date: 17.12.2020

Product code: 11089

Page 8 of 11

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-32-7	propylene carbonate					
	Acute fish toxicity	LC50 mg/l	5300	96 h	Leuciscus idus (golden orfe)	IUCLID
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna (Big water flea)	IUCLID
	aliphatic urethane acrylate					
	Acute algae toxicity	ErC50 mg/l	>0,68	72 h	(algae)	OECD 201
	Acute crustacea toxicity	EC50 mg/l	>1,2	48 h	(daphnia)	OECD 202
42978-66-5	tripropyleneglycol diacrylate					
	Acute fish toxicity	LC50 mg/l	4,5-10	96 h	Leuciscus idus (golden orfe)	
	Acute algae toxicity	ErC50	>28 mg/l	72 h	Desmodesmus subspicatus.	
	Acute crustacea toxicity	EC50 mg/l	88,7	48 h	Daphnia magna (Big water flea)	
2455-24-5	tetrahydrofurfuryl methacrylate THFMA purified grade					
	Acute fish toxicity	LC50 mg/l	34,7	96 h		GESTIS
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	Acute algae toxicity	ErC50 mg/l	>2,01	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	3,53	48 h	Daphnia magna (Big water flea)	
	Acute bacteria toxicity	(>1000 mg/l)		3 h	Activated sludge	
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide					
	Acute fish toxicity	LC50 mg/l	>0,09	96 h	Brachydanio rerio (zebra-fish)	OECD 203
	Acute algae toxicity	ErC50 mg/l	>0,26	72 h	Desmodesmus subspicatus.	OECD 201
	Acute crustacea toxicity	EC50 mg/l	>1,175	48 h	Daphnia magna (Big water flea)	OECD 202
	Crustacea toxicity	NOEC mg/l	>0,008	21 d	Daphnia magna (Big water flea)	OECD 211
	Acute bacteria toxicity	(>100 mg/l)		3 h	OECD 209	

12.2. Persistence and degradability

The product has not been tested.

according to Regulation (EC) No 1907/2006

freeprint® cast 385

Revision date: 17.12.2020

Product code: 11089

Page 9 of 11

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	aliphatic urethane acrylate			
	OECD 301B	22%	28	
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			
		0-10%	28	
	Not readily biodegradable (according to OECD criteria)			
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide			
	CO ₂ formation (% of the theoretical value).	1%	29	
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-32-7	propylene carbonate	-0,41
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	3,1
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	5,8

BCF

CAS No	Chemical name	BCF	Species	Source
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	47-55	Cyprinus carpio (Common Carp)	
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	<5	Cyprinus carpio (Common Carp)	OECD 305

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Not identified as PBT/ vPvB substances

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

according to Regulation (EC) No 1907/2006

freeprint® cast 385

Revision date: 17.12.2020

Product code: 11089

Page 10 of 11

<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
Marine transport (IMDG)	
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
Air transport (ICAO-TI/IATA-DGR)	
<u>14.1. UN number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.
<u>14.6. Special precautions for user</u>	No information available.
<u>14.7. Transport in bulk according to Annex II of Marpol and the IBC Code</u>	not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	3 - strongly hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Safety Data Sheet

according to Regulation (EC) No 1907/2006

freeprint® cast 385

Revision date: 17.12.2020

Product code: 11089

Page 11 of 11

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)