



**Safety Data Sheet  
according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

Hazardous according to criteria of Australian Safety and Compensation Council.

## 1 Identification

· **Product identifier**

· **Trade name:** **Adhesive liquid for prefd. wax parts**

· **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.

· **Application of the substance / the mixture** Auxiliary for manufacture of dental prothesis

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer Australia Pty Ltd  
Unit 20, 53 Lorraine Street  
Peakhurst, NSW 2210  
Australia

Tel: +61 (0) 2 9153 0311

· **Informing department:** see above

· **Emergency telephone number:**

Poison Information Number: Australia 13 11 26 & New Zealand 0800 764 766

## 2 Hazard(s) Identification

· **Classification of the substance or mixture**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard statements**

Highly flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

Store locked up.

· **Other hazards** -

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.



**Safety Data Sheet  
according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

**Trade name: Adhesive liquid for prefd. wax parts**

(Contd. of page 1)

### 3 Composition and Information on Ingredients

· **Chemical characterisation: Mixtures**

· **Description: -**

· **Dangerous components:**

CAS: 110-82-7 EINECS: 203-806-2	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 107-83-5 EINECS: 203-523-4	2-methylpentane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	5-10%
CAS: 142-82-5 EINECS: 205-563-8	heptane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	5-10%
CAS: 110-54-3 EINECS: 203-777-6	n-hexane Flam. Liq. 2, H225; Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	0-5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

· **Description of first aid measures**

· **After inhalation** Supply fresh air; consult doctor in case of symptoms.

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact**

Rinse opened eye for several minutes under running water. Then consult doctor.

· **After swallowing** Do not induce vomiting; instantly call for medical help.

· **Information for doctor**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire Fighting Measures

· **Extinguishing media**

· **Suitable extinguishing agents**

Water haze

Foam

Fire-extinguishing powder

Carbon dioxide

· **For safety reasons unsuitable extinguishing agents** Water with a full water jet.

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear self-contained breathing apparatus.

(Contd. on page 3)



**Safety Data Sheet  
according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

**Trade name: Adhesive liquid for prefd. wax parts**

· **Additional information -**

(Contd. of page 2)

## 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Use breathing protection against the effects of fumes/dust/aerosol.  
Keep away from ignition sources
- **Environmental precautions:**  
Prevent material from reaching sewage system, holes and cellars.  
Inform respective authorities in case product reaches water or sewage system.  
Do not allow product to reach sewage system or water bodies.
- **Methods and material for containment and cleaning up:**  
Dispose of the material collected according to regulations.  
Ensure adequate ventilation.  
Send for recovery or disposal in suitable containers.  
Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).
- **Reference to other sections**  
See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

## 7 Handling and Storage

- **Handling**
  - **Precautions for safe handling**  
Keep containers tightly sealed.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Use solvent-proof equipment.
  - **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect from heat.  
Protect against electrostatic charges.  
Highly volatile, flammable constituents are released during processing.  
Fumes can combine with air to form an explosive mixture.  
Flammable mixtures may be formed in empty containers.
- **Conditions for safe storage, including any incompatibilities**
  - **Storage**
    - **Requirements to be met by storerooms and containers:** Store in cool location.
    - **Information about storage in one common storage facility:** Not required.
    - **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed containers.
- **Specific end use(s)** No further relevant information available.

AUS

(Contd. on page 4)



**Safety Data Sheet  
according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

**Trade name: Adhesive liquid for prefd. wax parts**

(Contd. of page 3)

**8 Exposure controls and personal protection**

· **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

**110-82-7 cyclohexane**

NES (Australia)	Short-term value: 1050 mg/m <sup>3</sup> , 300 ppm Long-term value: 350 mg/m <sup>3</sup> , 100 ppm
PEL (USA)	Long-term value: 1050 mg/m <sup>3</sup> , 300 ppm
REL (USA)	Long-term value: 1050 mg/m <sup>3</sup> , 300 ppm
TLV (USA)	Long-term value: 344 mg/m <sup>3</sup> , 100 ppm

**107-83-5 2-methylpentane**

REL (USA)	Long-term value: 350 mg/m <sup>3</sup> , 100 ppm Peak limitation: 1800* mg/m <sup>3</sup> , 510* ppm *15-min
TLV (USA)	Short-term value: 3500 mg/m <sup>3</sup> , 1000 ppm Long-term value: 1760 mg/m <sup>3</sup> , 500 ppm

**142-82-5 heptane**

NES (Australia)	Short-term value: 2050 mg/m <sup>3</sup> , 500 ppm Long-term value: 1640 mg/m <sup>3</sup> , 400 ppm
PEL (USA)	Long-term value: 2000 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 350 mg/m <sup>3</sup> , 85 ppm Peak limitation: 1800* mg/m <sup>3</sup> , 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m <sup>3</sup> , 500 ppm Long-term value: 1640 mg/m <sup>3</sup> , 400 ppm

**110-54-3 n-hexane**

NES (Australia)	Long-term value: 72 mg/m <sup>3</sup> , 20 ppm
PEL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 180 mg/m <sup>3</sup> , 50 ppm
TLV (USA)	Long-term value: 176 mg/m <sup>3</sup> , 50 ppm Skin; BEI

· **Ingredients with biological limit values:**

**110-54-3 n-hexane**

BEI (USA)	0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2.5-Hexanedione without hydrolysis
-----------	---

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.  
Instantly remove any soiled and impregnated garments.  
Wash hands during breaks and at the end of the work.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

(Contd. on page 5)



**Safety Data Sheet**  
**according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

**Trade name: Adhesive liquid for prefd. wax parts**

(Contd. of page 4)

- **Protection of hands:**  
Solvent resistant gloves  
Check protective gloves prior to each use for their proper condition.  
recommended
  - **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
  - **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
  - **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**  
Butyl rubber, BR  
Nitrile rubber, NBR
- **Eye protection:** not absolutely necessary
- **Body protection:** Light weight protective clothing

## 9 Physical and Chemical Properties

### · Information on basic physical and chemical properties

#### · General Information

##### · Appearance:

- **Form:** Fluid
- **Colour:** Yellowish
- **Smell:** Characteristic
- **Odour threshold:** Not determined.

· **pH-value:** Not determined.

#### · Change in condition

- **Melting point/freezing point:** Not determined
- **Initial boiling point and boiling range:** 77 °C

· **Flash point:** -20 °C

· **Inflammability (solid, gaseous)** Not applicable.

#### · Ignition temperature:

· **Decomposition temperature:** Not determined.

· **Self-inflammability:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures is possible.

#### · Critical values for explosion:

- **Lower:** 1,2 Vol %
- **Upper:** 8,3 Vol %

· **Steam pressure at 20 °C:** 104 hPa

#### · Density at 20 °C

- **Relative density** 0,83 g/cm<sup>3</sup>
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.

(Contd. on page 6)



**Safety Data Sheet**  
**according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

**Trade name: Adhesive liquid for prefd. wax parts**

(Contd. of page 5)

· <b>Solubility in / Miscibility with</b> · <b>Water:</b>	Not miscible or difficult to mix
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b> · <b>dynamic at 20 °C:</b> · <b>kinematic at 20 °C:</b>	ca. 3000 mPas > 3600 mm <sup>2</sup> /s
· <b>Solvent content:</b> · <b>VOC EU</b>	60 %
· <b>Solids content:</b> · <b>Other information</b>	40 % No further relevant information available.

### 10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
  - **Conditions to be avoided:** No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** None
- **Additional information:** -

### 11 Toxicological Information

- **Information on toxicological effects**
  - **Acute toxicity**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>110-82-7 cyclohexane</b>		
Oral	LD50	12705 mg/kg (rat)
<b>110-54-3 n-hexane</b>		
Oral	LD50	28710 mg/kg (rat)

- **Primary irritant effect:**
  - **Skin corrosion/irritation** Irritant for skin and mucous membranes.
- **Respiratory or skin sensitisation** No sensitizing effect known.

### 12 Ecological Information

- **Toxicity**
  - **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
  - **Bioaccumulative potential** No further relevant information available.
  - **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
  - **Remark:** Very toxic for fish
- **Additional ecological information:**
  - **General notes:**  
Do not allow product to reach ground water, water bodies or sewage system.

(Contd. on page 7)



**Safety Data Sheet  
according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

**Trade name: Adhesive liquid for prefd. wax parts**

Danger to drinking water if even small quantities leak into soil.  
Also poisonous for fish and plankton in water bodies.  
Very toxic for aquatic organisms

(Contd. of page 6)

**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

**Waste treatment methods**

**Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

**UN-Number**

· **ADG, IMDG, IATA**

UN1133

**UN proper shipping name**

· **ADG**

· **IMDG**

· **IATA**

1133 ADHESIVES, special provision 640D  
ADHESIVES (CYCLOHEXANE, 2-methylpentane),  
MARINE POLLUTANT  
Adhesives

**Transport hazard class(es)**

· **ADG**



· **Class**

· **Label**

3 (F1) Flammable liquids.

3

· **IMDG**



· **Class**

· **Label**

3 Flammable liquids.

3

· **IATA**



· **Class**

3 Flammable liquids.

(Contd. on page 8)



**Safety Data Sheet**  
according to WHS Regulations

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

**Trade name: Adhesive liquid for prefd. wax parts**

(Contd. of page 7)

· <b>Label</b>	3
· <b>Packing group</b> · <b>ADG, IMDG, IATA</b>	II
· <b>Environmental hazards:</b> · <b>Marine pollutant:</b> · <b>Special marking (ADG):</b>	Product contains environmentally hazardous substances: cyclohexane, heptane Symbol (fish and tree) Symbol (fish and tree)
· <b>Special precautions for user</b> · <b>Kemler Number:</b> · <b>EMS Number:</b> · <b>Stowage Category</b>	Warning: Flammable liquids. 33 F-E, S-D B
· <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	-
· <b>ADG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>Transport category</b> · <b>Tunnel restriction code</b>	2 D/E
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1133 ADHESIVES, SPECIAL PROVISION 640D, 3, II

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard statements**

Highly flammable liquid and vapour.

Causes skin irritation.

(Contd. on page 9)

AUS



**Safety Data Sheet  
according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

**Trade name: Adhesive liquid for prefd. wax parts**

(Contd. of page 8)

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

Store locked up.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**