



**Safety Data Sheet
according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· **Product identifier**

· **Trade name: Paladon 65 liquid**

· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Manufacture of dental prothesis

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer Australia Pty Ltd
Unit 20, 53 Lorraine Street
Peakhurst, NSW 2210
Australia

Tel: +61 (0) 2 9153 0311

· **Informing department:** see above

· **Emergency telephone number:**

Poison Information Number: Australia 13 11 26 & New Zealand 0800 764 766

2 Hazard(s) Identification

· **Classification of the substance or mixture**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· **Label elements**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

methyl methacrylate

· **Hazard statements**

Highly flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

Store locked up.

· **Other hazards** -

(Contd. on page 2)



**Safety Data Sheet
according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

Trade name: Paladon 65 liquid

- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

(Contd. of page 1)

3 Composition and Information on Ingredients

- **Chemical characterisation: Mixtures**
 - **Description:** Product based on methacrylates

- **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	> 90%
CAS: 2082-81-7 EINECS: 218-218-1	tetramethylene dimethacrylate Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	0-5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- **Description of first aid measures**
 - **After inhalation** Supply fresh air; consult doctor in case of symptoms.
 - **After skin contact** Instantly wash with water and soap and rinse thoroughly.
 - **After eye contact** Rinse opened eye for several minutes under running water.
 - **After swallowing**
Rinse out mouth and then drink plenty of water.
In case of persistent symptoms consult doctor.
- **Information for doctor**
 - **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

- **Extinguishing media**
 - **Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.
 - **For safety reasons unsuitable extinguishing agents**
Water.
Water with a full water jet.
- **Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
 - **Protective equipment:** No special measures required.
- **Additional information** -

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

(Contd. on page 3)



**Safety Data Sheet
according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

Trade name: Paladon 65 liquid

(Contd. of page 2)

Do not flush with water or aqueous cleansing agents
Send for recovery or disposal in suitable containers.

Reference to other sections

See Section 13 for information on disposal.

See Section 8 for information on personal protection equipment.

7 Handling and Storage

Handling

Precautions for safe handling

Keep containers tightly sealed.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: Store in cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Store cool (not above 25 °C).

Store in cool, dry conditions in well sealed containers.

Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with critical values that require monitoring at the workplace:

80-62-6 methyl methacrylate

NES (Australia) 410 mg/m³, 100 ppm
Sk, Sen

PEL (USA) 410 mg/m³, 100 ppm

REL (USA) 410 mg/m³, 100 ppm

TLV (USA) Short-term value: 410 mg/m³, 100 ppm
Long-term value: 205 mg/m³, 50 ppm
SEN

DNELs

80-62-6 methyl methacrylate

Dermal worker industr., l.te., syst. 74.3 mg/Kg/d (human)

Inhalative worker industr., l.te., syst. 210 mg/m³ (human)

PNECs

80-62-6 methyl methacrylate

freshwater 0.94 mg/l (aqua)

Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 4)



Safety Data Sheet
according to WHS Regulations

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

Trade name: Paladon 65 liquid

(Contd. of page 3)

· **Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.
recommended

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber, BR

Nitrile rubber, NBR

· **Eye protection:** Safety glasses

· **Body protection:** Light weight protective clothing

9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

· **Colour:**

Colourless

· **Smell:**

Ester-like

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/freezing point:**

-48 °C

· **Initial boiling point and boiling range:**

101 °C

· **Flash point:**

10 °C

· **Inflammability (solid, gaseous)**

Not applicable.

· **Ignition temperature:**

430 °C

(Contd. on page 5)



Safety Data Sheet
according to WHS Regulations

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

Trade name: Paladon 65 liquid

(Contd. of page 4)

· Decomposition temperature:	Not determined.
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures is possible.
· Critical values for explosion:	
· Lower:	2,1 Vol %
· Upper:	12,5 Vol %
· Steam pressure at 20 °C:	47 hPa
· Density at 20 °C	0.940 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
· dynamic at 20 °C:	1 mPas
· kinematic:	Not determined.
· Solvent content:	
· VOC USA	910.9 g/l / 01.73 lb/gl
· VOC EU	913.2 g/l
· Other information	No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Conditions to be avoided:** No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** None
- **Additional information:**
If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

11 Toxicological Information

- **Information on toxicological effects**
 - **Acute toxicity**

· **LD/LC50 values that are relevant for classification:**

80-62-6 methyl methacrylate

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rab)
Inhalative	LC50/4 h	29.8 mg/l (rat)

(Contd. on page 6)



**Safety Data Sheet
according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

Trade name: Paladon 65 liquid

(Contd. of page 5)

2082-81-7 tetramethylene dimethacrylate

Oral	LD50	10120 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
 - **Skin corrosion/irritation** Irritant for skin and mucous membranes.
 - **Serious eye damage/irritation** No irritant effect.
 - **Respiratory or skin sensitisation** Sensitization possible by skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological Information

- **Toxicity**
 - **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
 - **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Small quantities can be polymerized with the matching system component(s) and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of the local authorities.
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| · UN-Number <ul style="list-style-type: none">· ADG, IMDG, IATA | 1247 |
| · UN proper shipping name <ul style="list-style-type: none">· ADG· IMDG, IATA | 1247 METHYL METHACRYLATE MONOMER, STABILIZED, solution
METHYL METHACRYLATE MONOMER, STABILIZED, solution |

(Contd. on page 7)



Safety Data Sheet
according to WHS Regulations

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

Trade name: Paladon 65 liquid

(Contd. of page 6)

· Transport hazard class(es)	
· ADG	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	
· ADG, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	
· Warning:	Warning: Flammable liquids.
· Kemler Number:	339
· EMS Number:	F-E,S-D
· Transport in bulk according to Annex II of Marpol and the IBC Code	
	Not applicable.
· Transport/Additional information:	
	-
· UN "Model Regulation":	
	UN1247, METHYL METHACRYLATE MONOMER, STABILIZED, solution, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

methyl methacrylate

· **Hazard statements**

Highly flammable liquid and vapour.

Causes skin irritation.

(Contd. on page 8)



**Safety Data Sheet
according to WHS Regulations**

Printing date 01.02.2021

Version number 4

Revision: 01.02.2021

Trade name: Paladon 65 liquid

(Contd. of page 7)

May cause an allergic skin reaction.

May cause respiratory irritation.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

Store locked up.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**