

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Revision date: 10.03.2021

die:master thinner**1956 0700**

Product code: 19560700_AUS_DD

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

die:master thinner 1956 0700

Further trade names

contained in:

1956 0800 die:master Set red

1956 0900 die:master Set blue

1956 1000 die:master Set gold/silver

1957 1000 die:master Set ivory

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

die:master thinner

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Renfert GmbH
Street: Untere Giesswiesen 2
Place: D-78247 Hilzingen
Telephone: +49 7731 8208-0
e-mail: info@renfert.com
Internet: www.renfert.com

Telefax: +49 7731 8208-70

Supplier

Company name: Durodent Dental Supplies
Street: Unit 6 / 51 Jersey Road
Place: VIC 3153 AUS Bayswater
Telephone: +61 (03) 9720 6700
e-mail: sales@durodent.com.au
Responsible Department: For non-urgent inquiries refer to:

Durodent Dental Supplies (Office) Phone: (03) 97206700

This number is only available during the following office hours:

Mon-Thurs 09:00am - 5:00pm / Friday 09:00 - 4:30pm AEST

1.4. Emergency telephone number:

Australien Poisons Information Centre (National) 13 11 26 - 24 Hours / 7 Days

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

2.2. Label elements

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master thinner

1956 0700

Revision date: 10.03.2021

Product code: 19560700_AUS_DD

Page 2 of 9

Regulation (EC) No. 1272/2008

Hazard components for labelling

butanone
pentan-3-one
n-butyl acetate

Signal word:

Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves and eye/face protection.
P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Solvents/Thinner

Hazardous components

| CAS No | Chemical name | | | Quantity |
|----------|--|--------------|------------------|-----------|
| | EC No | Index No | REACH No | |
| | GHS Classification | | | |
| 78-93-3 | butanone | | | 50 - 70 % |
| | 201-159-0 | 606-002-00-3 | 01-2119457290-43 | |
| | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066 | | | |
| 96-22-0 | pentan-3-one | | | 20 - 40% |
| | 202-490-3 | 606-006-00-5 | 01-2119531111-60 | |
| | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3, STOT SE 3; H225 H319 H335 H336 EUH066 | | | |
| 123-86-4 | n-butyl acetate | | | 5 - 15% |
| | 204-658-1 | 607-025-00-1 | 01-2119485493-29 | |
| | Flam. Liq. 3, STOT SE 3; H226 H336 EUH066 | | | |

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Revision date: 10.03.2021

die:master thinner**1956 0700**

Product code: 19560700_AUS_DD

Page 3 of 9

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated, saturated clothing immediately.

After inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder, Carbon dioxide (CO₂), alcohol resistant foam, Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

Thermal decomposition can lead to the escape of irritating gases and vapours.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Provide adequate ventilation.

Use personal protection equipment.

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master thinner

1956 0700

Revision date: 10.03.2021

Product code: 19560700_AUS_DD

Page 4 of 9

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only in well-ventilated areas.

Avoid contact with eyes and skin.

When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Vapours can form explosive mixtures with air.

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)Please refer to our internet website for more information: www.renfert.com**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|----------|-----------------------------------|-----|-------------------|-----------|---------------|--------|
| 78-93-3 | Butan-2-one (methyl ethyl ketone) | 200 | 600 | | TWA (8 h) | WEL |
| | | 300 | 899 | | STEL (15 min) | WEL |
| 123-86-4 | Butyl acetate | 150 | 724 | | TWA (8 h) | WEL |
| | | 200 | 966 | | STEL (15 min) | WEL |
| 96-22-0 | Pentan-3-one | 200 | 716 | | TWA (8 h) | WEL |
| | | 250 | 895 | | STEL (15 min) | WEL |

Biological Monitoring Guidance Values (EH40)

| CAS No | Substance | Parameter | Value | Test material | Sampling time |
|---------|-------------|-------------|-----------|---------------|---------------|
| 78-93-3 | Butan-2-one | butan-2-one | 70 µmol/L | urine | Post shift |

8.2. Exposure controls**Appropriate engineering controls**

Safe handling: see section 7

Protective and hygiene measures

Do not breathe vapour.

Avoid contact with skin, eyes and clothes.

Wash hands before breaks and after work.

Keep away from food, drink and animal feedingstuffs.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

die:master thinner**1956 0700**

Revision date: 10.03.2021

Product code: 19560700_AUS_DD

Page 5 of 9

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,5 mm

Breakthrough time: ≥ 60 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Respiratory protection

Use only in well-ventilated areas.

Usually no personal respiratory protection necessary.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|-----------------|----------------|
| Physical state: | Liquid |
| Colour: | colourless |
| Odour: | characteristic |

Test method

| | |
|-----------|----------------|
| pH-Value: | not applicable |
|-----------|----------------|

Changes in the physical state

| | |
|----------------|----------------|
| Melting point: | not determined |
|----------------|----------------|

| | |
|--|-------|
| Boiling point or initial boiling point and | 79 °C |
|--|-------|

boiling range:

| | |
|--------------|-------------------------|
| Flash point: | - 1,5 °C DIN 51755 (cc) |
|--------------|-------------------------|

Flammability

| | |
|---------------|----------------|
| Solid/liquid: | not applicable |
|---------------|----------------|

| | |
|------|----------------|
| Gas: | not applicable |
|------|----------------|

Explosive properties

not explosive.

Vapours can form explosive mixtures with air.

| | |
|-------------------------|------------|
| Lower explosion limits: | 1,2 vol. % |
|-------------------------|------------|

| | |
|-------------------------|-------------|
| Upper explosion limits: | 11,5 vol. % |
|-------------------------|-------------|

| | |
|----------------------------|--------|
| Auto-ignition temperature: | 370 °C |
|----------------------------|--------|

Self-ignition temperature

| | |
|--------|----------------|
| Solid: | not applicable |
|--------|----------------|

| | |
|------|----------------|
| Gas: | not applicable |
|------|----------------|

| | |
|----------------------------|----------------|
| Decomposition temperature: | not determined |
|----------------------------|----------------|

| | |
|------------------|---------|
| Vapour pressure: | 105 hPa |
|------------------|---------|

(at 20 °C)

| | |
|---------------------|-----------------------------|
| Density (at 20 °C): | 0,7 - 0,9 g/cm ³ |
|---------------------|-----------------------------|

| | |
|-------------------|------------|
| Water solubility: | Immiscible |
|-------------------|------------|

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

die:master thinner**1956 0700**

Revision date: 10.03.2021

Product code: 19560700_AUS_DD

Page 6 of 9

| | |
|--|----------------|
| Partition coefficient n-octanol/water: | not determined |
| Viscosity / dynamic: | not determined |
| Viscosity / kinematic: | not determined |
| Relative vapour density: | not determined |
| Evaporation rate: | not determined |
| Solvent content: | 100% |

9.2. Other information

| | |
|----------------|-----|
| Solid content: | 0 % |
|----------------|-----|

SECTION 10: Stability and reactivity**10.1. Reactivity**

Vapours can form explosive mixtures with air.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (pentan-3-one)

May cause drowsiness or dizziness. (butanone; pentan-3-one)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information**12.1. Toxicity**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

die:master thinner**1956 0700**

Revision date: 10.03.2021

Product code: 19560700_AUS_DD

Page 7 of 9

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

| CAS No | Chemical name | | | |
|---------|---|-------|----|--------|
| | Method | Value | d | Source |
| | Evaluation | | | |
| 78-93-3 | butanone | | | |
| | OECD 301D | 98 % | 28 | |
| | Readily biodegradable (according to OECD criteria). | | | |

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|---------|---------------|---------|
| 96-22-0 | pentan-3-one | 0,82 |

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.7. Other adverse effects

No information available.

Further information

The product has not been tested. The statement is derived from the properties of the single components. Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

| | |
|--|-------------------|
| 14.1. UN number: | UN 1263 |
| 14.2. UN proper shipping name: | FARBZUBEHÖRSTOFFE |
| 14.3. Transport hazard class(es): | 3 |
| 14.4. Packing group: | II |
| Hazard label: | 3 |

**Marine transport (IMDG)**

| | |
|--|------------------------|
| 14.1. UN number: | UN 1263 |
| 14.2. UN proper shipping name: | PAINT RELATED MATERIAL |
| 14.3. Transport hazard class(es): | 3 |

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master thinner

1956 0700

Revision date: 10.03.2021

Product code: 19560700_AUS_DD

Page 8 of 9

14.4. Packing group:

II

Hazard label:

3



Marine pollutant:

no

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number:**

UN 1263

14.2. UN proper shipping name:

PAINT RELATED MATERIAL

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:

No

14.6. Special precautions for user

Additional information: see section 6, 7, 8

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC):

100 %

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

Additional information

REGULATION (EC) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on substances that deplete the ozone layer: not applicable

REGULATION (EU) 2019/1021 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on persistent organic pollutants

: not applicable

REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the export and import of hazardous chemicals: not applicable

SECTION 16: Other information**Abbreviations and acronyms**

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LD50: lethal dose, 50%

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

die:master thinner**1956 0700**

Revision date: 10.03.2021

Product code: 19560700_AUS_DD

Page 9 of 9

LC50: lethal concentration, 50%

EC50: half maximal effective concentration

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

| Classification | Classification procedure |
|--------------------|--------------------------|
| Flam. Liq. 2; H225 | On basis of test data |
| Eye Irrit. 2; H319 | Calculation method |
| STOT SE 3; H335 | Calculation method |
| STOT SE 3; H336 | Calculation method |

Relevant H and EUH statements (number and full text)

| | |
|--------|---|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)